查询BY329供应商

Rectifier diodes fast, soft-recovery

BY329F, BY329X series

FEATURES

- Low forward volt drop
- Fast switching
- Soft recovery characteristic
- High thermal cycling performance
- Isolated mounting tab

SYMBOL



QUICK REFERENCE DATA

V_R = 800 V/ 1000 V/ 1200 V

$I_{F(AV)}$ = 8 A

$I_{FSM} \leq$ 65 A

$t_{rr} \leq$ 145 ns

GENERAL DESCRIPTION

Glass-passivated double diffused rectifier diodes featuring low forward voltage drop, fast reverse recovery and soft recovery characteristic. The devices are intended for use in TV receivers, monitors and switched mode power supplies.

The BY329F series is supplied in the conventional leaded SOD100 package.
The BY329X series is supplied in the conventional leaded SOD113 package.

PINNING

PIN	DESCRIPTION
1	cathode
2	anode
tab	isolated

SOD100



SOD113



LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.			UNIT
		BY329F / BY329X		**-800**	**-1000**	**-1200**	
V_{RSM}	Peak non-repetitive reverse voltage		-	800	1000	1200	V
V_{RRM}	Peak repetitive reverse voltage		-	800	1000	1200	V
V_{RWM}	Crest working reverse voltage		-	600	800	1000	V
$I_{F(AV)}$	Average forward current[1]	square wave; δ = 0.5; $T_{hs} \leq$ 83 ˚C	-	8			A
		sinusoidal; a = 1.57; $T_{hs} \leq$ 90 ˚C	-	7			A
$I_{F(RMS)}$	RMS forward current		-	11			A
I_{FRM}	Peak repetitive forward current	t = 25 µs; δ = 0.5; $T_{hs} \leq$ 83 ˚C	-	16			A
I_{FSM}	Peak non-repetitive forward current.	t = 10 ms	-	65			A
		t = 8.3 ms sinusoidal; T_j = 150 ˚C prior to surge; with reapplied $V_{RWM(max)}$	-	71			A
I^2t	I^2t for fusing	t = 10 ms	-	28			A^2s
T_{stg}	Storage temperature		-40	150			˚C
T_j	Operating junction temperature		-	150			˚C

1. Neglecting switching and reverse current losses.

ISOLATION LIMITING VALUE & CHARACTERISTIC

T_{hs} = 25 ˚C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_{isol}	Peak isolation voltage from both terminals to external heatsink	SOD100 package; R.H. ≤ 65%; clean and dustfree	-	-	1500	V
V_{isol}	R.M.S. isolation voltage from both terminals to external heatsink	SOD113 package; f = 50-60 Hz; sinusoidal waveform; R.H. ≤ 65%; clean and dustfree	-	-	2500	V
C_{isol}	Capacitance from pin 1 to external heatsink	f = 1 MHz	-	10	-	pF

THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th\ j\text{-}hs}$	Thermal resistance junction to heatsink	with heatsink compound	-	-	4.8	K/W
		without heatsink compound	-	-	5.9	K/W
$R_{th\ j\text{-}a}$	Thermal resistance junction to ambient	in free air.	-	55	-	K/W

STATIC CHARACTERISTICS

T_j = 25 ˚C unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_F	Forward voltage	I_F = 20 A	-	1.5	1.85	V
I_R	Reverse current	$V_R = V_{RWM}$; T_j = 125 ˚C	-	0.1	1.0	mA

DYNAMIC CHARACTERISTICS

T_j = 25 ˚C unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
t_{rr}	Reverse recovery time	I_F = 1 A; $V_R \geq$ 30 V; $-dI_F/dt$ = 50 A/µs	-	125	145	ns
Q_s	Reverse recovery charge	I_F = 2 A; $V_R \geq$ 30 V; $-dI_F/dt$ = 20 A/µs	-	0.5	0.7	µC
dI_R/dt	Maximum slope of the reverse recovery current	I_F = 2 A; $-dI_F/dt$ = 20 A/µs	-	50	60	A/µs



Fig.1. Definition of t_{rr}, Q_s and I_{rrm}



Fig.4. Maximum non-repetitive rms forward current. $I_F = f(t_p)$; sinusoidal current waveform; T_j = 150˚C prior to surge with reapplied V_{RWM}.



Fig.2. Maximum forward dissipation, $P_F = f(I_{F(AV)})$; square wave current waveform; parameter D = duty cycle = t_p/T.



Fig.5. Typical and maximum forward characteristic; $I_F = f(V_F)$; parameter T_j



Fig.3. Maximum forward dissipation, $P_F = f(I_{F(AV)})$; sinusoidal current waveform; parameter a = form factor = $I_{F(RMS)}/I_{F(AV)}$.



Fig.6. Maximum Q_s at T_j = 25˚C and 150˚C



Fig.7. Maximum t_{rr} measured to 25% of I_{rrm}; T_j = 25˚C and 150˚C



Fig.9. Transient thermal impedance $Z_{th} = f(t_p)$



Fig.8. Typical junction capacitance C_d at f = 1 MHz, T_j = 25˚C

MECHANICAL DATA

Dimensions in mm

Net Mass: 2 g



Fig.10. SOD100; The seating plane is electrically isolated from all terminals.

Notes
1. Refer to mounting instructions for F-pack envelopes.
2. Epoxy meets UL94 V0 at 1/8".

MECHANICAL DATA

Dimensions in mm

Net Mass: 2 g



Fig.11. SOD113; The seating plane is electrically isolated from all terminals.

Notes
1. Refer to mounting instructions for F-pack envelopes.
2. Epoxy meets UL94 V0 at 1/8".

DEFINITIONS

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	
© **Philips Electronics N.V. 1998**	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.